

- Expandable To 48 Fully Programmable Hardwire And/Or Wireless Zones
- Maximum Of 24 Keypads With Up To 8 Per Partition
- Up To 8 True Partitions With Separate Account Codes, Entry/Exit Delays, And Feature Selections For Each Partition
- ITI Wireless Technology With Up To 48 Supervised Zones
- Hardwire Expansion Up To 48 Zones.
- Supports SIA And Contact ID Communication Formats



NX-148E KEYPAD

NX-1448E KEYPAD

## The Power of One — from CADDX

### Overview

The NX-8 is a full-featured security system that uses advanced technology for burglary, fire and environmental detection. The NX-8 is a flexible security system that is both easy to install and simple to use. With eight partitions and up to 48 zones, the NX-8 can handle big or small residential and commercial security needs.

### High Standards

The panel comes standard with eight hardwire zone inputs. Four programmable outputs can be set up to activate external devices during an alarm or other system event. The Modular design allows for complete integration of multiple systems within one enclosure. Adding more zones or expanding capability is fast and easy.

### Easy Expansion

Expand the NX-8 capabilities by adding the optional NX-216 Zone Expander Module. Modular design allows NetworX modules to slide into the enclosure and adds up to 48 additional zones. Add up to eight outputs with the NX-508E to become the director of lights, home automation and industrial process control with X-10 or other power outputs.

Expand the system even further with a phone interface/voice module for on-site and off-site system control using touchtone phones.

### Effortless Programming

Conduct quick and easy on-site programming with alphanumeric keypads and a menu driven text interface. Off-site programming is also available with the DL-900 software for Windows.

# CADDX NX-8



## CADDX® NX-8 Control Panel

### AVAILABLE KEYPAD STYLES



LED



FIXED DISPLAY WITH REMOVABLE DOOR



LED WITH REMOVABLE DOOR



LCD WITH REMOVABLE DOOR

### SPECIFICATIONS

Operating power	16VDC 40VA
Auxiliary power	
w/40VA or 50VA transformer	1 Amps
w/NX-320E power supply	3 Amps*
Loop resistance	
For standard loop	300 Ohms Maximum
For 2-wire smokes	30 Ohms Maximum
Built-in siren driver	2 Tone (Steady & Yelp)
Alarm current available (if above driver is not used)	2.5 Amps
Loop response	Selectable 50ms or 500ms
Operating temperature	32F to 102 °F (0 to 49 °C)
LCD keypad dimensions	6.4"W 4.0"H 1.1" D
LED keypad dimensions	6.4"W 5.3"H 1.0" D
Keypad material	White / ABS
Enclosure dimensions	11.25"W 11.25"H 3.5" D
Enclosure color	Off White
Shipping weight	9 lbs

\*When using the NX-320E (w/50VA transformer) rated at 2 Amps and NX-8 (w/40VA or 50VA transformer) rated at 1 Amp, the combined available power is 3 Amps.

### ORDERING INFORMATION

MODEL No.	DESCRIPTION
NX-8	8-zone control only. Keypad and transformer sold separately.
NX-8-KIT	8-zone control with NX-108E keypad and transformer.
NX-848-KIT	8-zone control with NX-148E LCD keypad and transformer.
NX-108E	8-zone LED keypad.
NX-1316E	16-zone LED keypad with removable door.
NX-1448E	48-zone fixed display LCD keypad.
NX-148E	48-zone custom display LCD keypad with removable door.
NX-216	16-zone hardwire expander module.
NX-408E/416E/448E	8, 16, 48-zone wireless expander receivers.

Contact your local distributor or Interlogix representative for a complete list of Caddx parts and accessories.



SECURITY & LIFE SAFETY GROUP

1420 NORTH MAIN GLADEWATER, TX 75647  
SALES USA & CANADA: 800-547-2556  
TECHNICAL SERVICE: 800-727-2339  
www.caddx.com

© 2001 Interlogix, Inc.  
Interlogix reserves the right to change specifications without notice.  
Caddx® is a registered trademark of Interlogix, Inc.